






K2 – CEILING SUSPENSION GRIDS



IMPERIAL SYSTEM UNIT T-24 (15/16") SEISMIC

| Purpose | Profile | Length (mm) | Width (mm) | Height (mm) | Thickness (mm) | Diagram |
|------------------------------------|-----------------|-------------|------------|-------------|----------------|---|
| Seismic / Heavy duty T-24 (15/16") | Wall Trim | 3050 | 24 | 24 | 0,50 |  |
| | Wall Trim | 3050 | 24 | 24 | 0,40 |  |
| | Main Runner | 3660 | 24 | 38 | 0,35 |  |
| | Long Cross Tee | 1220 | 24 | 28 | 0,35 |  |
| | Short Cross Tee | 610 | 24 | 28 | 0,35 |  |

Advantages

1. Seismic system / Heavy Duty.
2. Maximum load capacity 20 kg / ml, ideal for metal tiles or wooden tiles.
3. High traction and compression capacity.
4. Ideal for hidden or semi-hidden demountable tile.
5. Quick and easy alignment and leveling during installation or maintenance.
6. High resistance to oxidation and corrosion.

Our ceiling suspension grids are double web cold-rolled sections, at the same time are manufactured from hot-dipped galvanized steel, in order to avoid corrosion and enhance mechanical strength to shock and abrasion, conforms to standard. JIS G3302 SGCC. Product has a pre-painted finish look which provides and guarantees a very high-quality system.

The main runner is slotted for cross tees at 150 mm or 6 " centers to give maximum flexibility in the ceiling lay out.